DAXOM®

Daxom

Floor Type Electrical Boiler with Tank

Comfort and Confidence suits to your life

CE





Floor Type Electrical Boiler with Tank

Daxom 10~24 kW



UKDAX-80Y**BT Model

GENERAL SPECIFICATIONS

- Instant and continious hot water with 80 and 120 liter stainless steel fast boiler
- High efficiency with full modulation operation
- Touch operated and easy using stylish control pannel
- Can be operated 3 phase or single phase
- Can be identifable 7 programs as daily or weekly
- Can be identifable different operation temperature for every programme
- Floor heating low temperature and radiator heating options
- Compatible operation with solar energy system
- Unti blockage system for pump and three way valve
- Provides hygienic water with anti-legionary function
- No drainage problem because of there is expansion tank at boiler line
- Ready to use hot water within 10 min
- Circulation pump with integrated cycle control
- Protection against to corrosion with Mg anot
- Power Setting with 3 level
- Summer – Winter position option
- Doublr freezing prevention system
- Over heat security system
- Flow control security system
- Operation without water security system
- Double over pressure security system
- Automatic air relief cock
- Erp pump
- Second pump connection option
- %99 efficiency

Technical Informations				
Model	Power (kW)	Boiler Capacity (l)	Weight Without Water (kg)	Dimensions H*W*D (mm)
3~400 V, 50 Hz Electrical Boiler with Tank				
UKDAX-80Y10BT	10	80	55	836*600*590
UKDAX-80Y12BT	12	80	55	836*600*590
UKDAX-80Y16BT	16	80	55	836*600*590
UKDAX-80Y18BT	18	80	55	836*600*590
UKDAX-80Y20BT	20	80	55	836*600*590
UKDAX-80Y24BT	24	80	55	836*600*590
UKDAX-120Y10BT	10	120	65	1152*600*590
UKDAX-120Y12BT	12	120	65	1152*600*590
UKDAX-120Y16BT	16	120	65	1152*600*590
UKDAX-120Y18BT	18	120	65	1152*600*590
UKDAX-120Y20BT	20	120	65	1152*600*590
UKDAX-120Y24BT	24	120	65	1152*600*590
1~220 V, 50 Hz Electrical Boiler with Tank				
UKDAX-80Y10BM	10	80	55	836*600*590
UKDAX-80Y12BM	12	80	55	836*600*590
UKDAX-80Y16BM	16	80	55	836*600*590
UKDAX-80Y18BM	18	80	55	836*600*590
UKDAX-120Y10BM	10	120	65	1152*600*590
UKDAX-120Y12BM	12	120	65	1152*600*590
UKDAX-120Y16BM	16	120	65	1152*600*590
UKDAX-120Y18BM	18	120	65	1152*600*590



UKDAX-120Y**BT Model

Technical Informations		Radiator	Tap Water
Min. Operation Pressure	bar	1	-
Max. Operation Pressure	bar	3	8
Min. Setting Temperature	°C	10	35
Max. Setting Temperature	°C	80	65
Connections	inch	3/4	1/2

Stainless steel fast boiler



Circulation pump with cycle control



2 liter boiler expansion tank



7 liter radiator cycle expansion tank



Built in Installation Implementation



Isı Cihazları Sanayi ve Ticaret Limited Şirketi
Namık Kemal Mahallesi Marmara Caddesi No:74
34702 - ÜMRANİYE / İSTANBUL / TÜRKİYE
Tel: (0216) 369 85 36 - 360 23 40 - 360 71 21

www.daxom.com.tr

DAXOM®

Isı Cihazları San. ve Tic. Ltd. Şti, reserves the right to modify the characteristics and information contained in this document at any time and without advance warning.