Heat Product Of Life DAXOM®

Daxom / THERMOTANK

Gas Fired Condensing Boiler



EFFICIENCY ★★★★

According To European Union EEC 92/42 Standards

CE

High efficiency hot water by *Daxom Thermotank* condensing technology

DAXOM®

Heat Product Of Life

Gas Fired Condensing Boiler

Daxom / THERMOTANK 25 kW ~ 65 kW with 160 ~ 2000 liter





Touch Operated LCD CONTROL PANNEL

TECHNICAL SPECIFICATIONS	UNIT	UKDAX-160GB25	UKDAX-160GB35	UKDAX-200GB25	UKDAX-200GB35	UKDAX-300GB25	UKDAX-300GB35	UKDAX-400GB25	UKDAX-400GB35	UKDAX-500GB65	UKDAX-800GB65	UKDAX-1000GB65	UKDAX-1500GB65	UKDAX-2000GB65
Gas Types	-	G20/G30												
Pipe Types	-	C13,C33,C43,C53,C83,C93												
Boiler Volume	l	160	160	200	200	300	300	400	400	500	800	1000	1500	2000
Heat Power	kW	25	35	25	35	25	35	25	35	65	65	65	65	65
Instant Hot Water Supply (Δt=35°C)*	l/min	11	15	11	15	11	15	11	15	27	27	27	27	27
Dimensions														
Height	mm	1710	1710	1960	1960	1699	1699	2004	2004	2274	2274	2274	2792	2822
Diameter	mm	630	630	630	630	830	830	830	830	830	1010	1010	1140	1280
Connections														
Water Inlet /Outlet	inch	1									1 1/2			
Re-Circulation	inch	3/4									1			
Cleaning Cover	inch	4									6			
Thermometer / Sensor	inch	1/2												
Gas Inlet	inch	3/4												
Condensing Outlet	inch	1/2												
Fresh Air Inlet / Exhaust Gas Outlet	mm	80 / 80												
Others														
Magnesium Anode Quantity	pcs	1									2			
Isolation Type	-	STONE WOOL												
Isolation Thickness	mm	60												
Outer Cover	-	VINLEKS ARTIFICIAL LEATHER												
Interior Surface Cover	-	STAINLESS STEEL												
Min Operation Pressure	bar	7												
Test Pressure	bar	10,5												

*Values are Rounded.

GENERAL SPECIFICATIONS

- Opreates Both NG and LPG
- Premix Burner
- Stainless Tank
- %105 Efficiency
- 7 bar Operation Pressure
- High Combustion Efficiency by PWM Control Fan
- Adjustable Water Temperature between 35 and 60 °C (Max 90 °C for Special Situations)
- Economic Usage Setting Options
- Weekly and Daily 21 Different Time Programs
- Low Heat Loss by Increased Isolation
- Automatic Opearation Against to Bacterial Growth
- Over Temperature Safety Thermostad
- Freezing Prevention
- Cathodic Protection by Magnesium Anode Rod
- Sound Alarm for Heatexchanger Encrustation
- Sound Alarm for Unefficiency Combustion
- Safety System without Water Operation
- Vinleks Artificial Leather External Cover
- External Touch - Opreated LCD Display Control Pannel
- Silent Operation

EFFICIENCY

According To European Union EEC 92/42 Standards CE

Isı Cihazları Sanayi ve Ticaret Limited Şirketi

Namık Kemal Mahallesi
Marmara Caddesi No:74
34702 Ümraniye
İSTANBUL / TÜRKİYE

+90 216 369 85 36
+90 216 360 23 40
+90 216 360 71 21

www.daxom.com.tr

DAXOM®

Heat Product Of Life

Navidens

Turkey
Discover the potential

© 2023 Daxom Türkiye. All Rights are reserved.

*Isı Cihazları San. ve Tic. Ltd. Şti., reserves the right to modify thetechnical specifications and information contained in this catolog at any time and without prior warning.